



# iRTC relay- delays de-energizing a load upon opening- 1 O/C - Uc 24-240VAC/24VDC

Local distributor code: 399365414 A9E1606

EAN Code: 3606480377433

### Main

| Relay application           | Time delay relay                                    |
|-----------------------------|---|
| Time delay type             | Delays de-energizing of a load upon contact opening |
| Range                       | Acti9   |
| Product name                | IRT   |
| Device short name           | iRTC  |
| Signal contacts composition | 1 C/O   |

| Complementary                  |  |
|--------------------------------|--|
| [le] rated operational current | 8 A at 250 V AC<br>8 A at 250 V DC<br>0.01 A at 5 V DC |
| Impulse duration               | > 100 ms   |
| Local signalling               | LED, flashing for time delay                           |
| Type of setting                | Rotary knob: time delay configuration                  |
| Time delay range               | 0.1360000 s  |
| Accuracy error                 | +/- 10 %   |
| Repeat accuracy                | +/- 0.5 %  |
| [Uc] control circuit voltage   | 24240 V AC 50/60 Hz<br>24 V DC                         |
| [Us] rated supply voltage      | 24240 V AC at 50/60 Hz<br>24 V DC                      |
| Mounting mode                  | Fixed  |
| Mounting support               | 35 mm symmetrical DIN rail                             |
| 9 mm pitches                   | 2  |
| Height                         | 93 mm  |
| Width                          | 18 mm  |
| Depth                          | 72 mm  |
| Net weight                     | 0.065 kg   |
| Colour                         | White  |
| Mechanical durability          | 5000000 cycles   |
| Electrical durability          | AC-1: 100000 cycles                                    |

| Undervoltage behaviour                | 100 ms  |  |
|---------------------------------------|---|--|
| Connections - terminals               | Tunnel type terminals for 2 cable(s) 1.5 mm² flexible with cable end Tunnel type terminals for 2 cable(s) 1.5 mm² flexible without cable end Tunnel type terminals for 2 cable(s) 2.5 mm² rigid with cable end Tunnel type terminals for 2 cable(s) 2.5 mm² rigid without cable end |  |
| Environment                           |   |  |
| IP degree of protection               | IP20  |  |
| Immunity to microbreaks               | 20 ms   |  |
| Ambient air temperature for operation | -555 °C   |  |
| Ambient air temperature for storage   | -4070 °C  |  |
| Packing Units                         |   |  |
| Unit Type of Package 1                | PCE   |  |

| Unit Type of Package 1       | PCE      |
|------------------------------|----------|
| Number of Units in Package 1 | 1        |
| Package 1 Height             | 2 cm     |
| Package 1 Width              | 7.5 cm   |
| Package 1 Length             | 10.2 cm  |
| Package 1 Weight             | 79 g     |
| Unit Type of Package 2       | S02      |
| Number of Units in Package 2 | 40       |
| Package 2 Height             | 15 cm    |
| Package 2 Width              | 30 cm    |
| Package 2 Length             | 40 cm    |
| Package 2 Weight             | 3.621 kg |
| Package 3 Height             | 30.0 cm  |

## Offer Sustainability

| Sustainable offer status   | Green Premium product  |
|----------------------------|--|
| REACh Regulation           | REACh Declaration  |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free               | Yes  |
| China RoHS Regulation      | China RoHS declaration   |
| RoHS exemption information | Yes  |
| Environmental Disclosure   | Product Environmental Profile  |
| Circularity Profile        | End of Life Information  |

### **Contractual warranty**

Warranty 18 months

### Recommended replacement(s)