

**EMERGENCY COMPACT BULKHEAD IP65 1W 150LM 3HR MAINTAINED OR NON-MAINTAINED 6000K MANUAL TEST INCLUDING UP DOWN LEFT RIGHT LEGENDS INTEGRAL LED**

ILEMBH028

**Details**

<b>Quick Order Code:</b>	583198
<b>Barcode:</b>	5055788288695
<b>Category:</b>	Emergency
<b>Range Name:</b>	Emergency Bulkhead
<b>Product Type:</b>	Emergency Bulkhead
<b>Product Body Finish:</b>	Matt white
<b>Market Segment:</b>	Indoor and Outdoor Commercial, Industrial, Residential
<b>Finish:</b>	Matt White
<b>Warranty (Years):</b>	3
<b>CE RoHS:</b>	Yes

**Physical Data**

<b>Product Length (mm):</b>	231
<b>Product Depth (mm):</b>	49
<b>Product Width (mm):</b>	116
<b>Product Weight (g):</b>	277
<b>Optic:</b>	Polycarbonate diffuser
<b>Material:</b>	Polycarbonate
<b>Construction:</b>	Plastic
<b>Bulb or Luminaire Shape:</b>	Rectangle
<b>Luminaire Fixing:</b>	Ceiling, Wall
<b>Placement / Application:</b>	Indoor, Outdoor, General Lighting

**Electrical Data**

<b>Power Consumption (W) :</b>	1
<b>Power Factor:</b>	0.5
<b>Voltage Range (v):</b>	220-240
<b>Amperage (mA):</b>	375
<b>Input Voltage (V):</b>	220-240
<b>Battery Configuration:</b>	LiFePo4
<b>Dimming:</b>	Non-Dimmable

<b>Driver Included:</b>	Yes
<b>Electric Current:</b>	AC
<b>Emergency Battery Life (years):</b>	3
<b>Emergency Lumens (lm):</b>	150
<b>Emergency Type:</b>	Non-Maintained
<b>EN:</b>	EN-60598
<b>LVD Certified:</b>	Yes

## Light Data

<b>Luminous Flux in Lumens (lm):</b>	150
<b>Correlated Colour Temperature (CCT) (K):</b>	6000
<b>Colour Temperature:</b>	6000K - Cool Daylight
<b>Colour Temperature Name:</b>	Daylight
<b>Beam Angle:</b>	120
<b>Colour Rendering Index (CRI):</b>	70
<b>Frequency Range (Hz):</b>	50/60
<b>Instant on (Less than 1 second):</b>	Yes
<b>LED Size (mm):</b>	2835
<b>LED Type:</b>	Surface mounted device (SMD)
<b>Lifetime (hours):</b>	50000
<b>Lumens in Emergency mode (lm):</b>	150
<b>Switching Cycles:</b>	15000
<b>Useful Lumens (lm):</b>	150

## Environment

<b>EN:</b>	EN-60598
<b>LVD Certified:</b>	Yes
<b>CE RoHS:</b>	Yes
<b>EU Luminaire:</b>	L
<b>Hg 0% (Mercury Free):</b>	Yes
<b>IK Rating (Impact Protection):</b>	IK07
<b>IP Rating (Ingress Protection):</b>	IP65
<b>Lowest Operating Temperature (°C):</b>	5
<b>Maximum Operating Temperature (°C):</b>	40

## Packaging

<b>Package Weight (g):</b>	332
<b>Package Length (mm):</b>	116
<b>Package Width (mm):</b>	53
<b>Package Depth (mm):</b>	234