

JCEM002/50

Emergency Remote Pack

Fire-rated Downlight Emergency Remote Pack 2W IP20 LifePo4 Battery

Features & Benefits

- Plug and play connectors for quick and simple installation
- For use with V50 and V50 Pro Fire-rated downlights
- 2W maximum output
- LifePo4 battery
- 5 Year Warranty including battery



General Information

Mounting

Environment

Suitable For Zones

Product Group

Product Range

Trade Name

Color Finish

Product Shape

Overall Dimensions

Light Source

Product Weight(kg)

Additional Information

Recommended product location

Product Aperture Size

IP Rating

Origin of manufacturer

Warranty

Operation Type

Lighting Product Type 1

Lighting Product Type 2

Recessed

Indoor

Outside Zone 2

Emergency Remote Pack

Emergency

Emergency Range

Green

Rectangular

234.2(L) x 49.2(W) x 36.7(H)

LED

0.45

LED indicator cut out 20mm

Ceiling voids(recessed applications)

60mm

IP20

Made in China

5 Year Warranty (5 years on batteries)(See Website for terms and conditions)

Maintained only

Emergency Lighting

Accessory

Electrical

Voltage Rating	220-240
Primary Running Current(Amp)	0.05
Inrush current(Amps)	7
Operating Frequency Hz	50/60Hz
Secondary running current(mA)	220-25
Luminaire Circuit Wattage	2W max Output
Class	II
Power Factor Correction	0.5
Input Electrical Connections	N(Neutral)E(Earth)Usw/L(Unswitched Live)Sw/L(switched Live) loop-in loop-out

Emergency Data

Load Voltage(DC)	9-75
LOR % in Emergency Mode	To calculate the LOR% please use the formula shown: 2.4W Power in EM mode ÷ Fitting Wattage (e.g. 10W) x 100 = LOR % (2.4 ÷ 10 x 100=24%)
Minimum Battery run time	3
Recharge Time	24hrs
Inverter PFC	0.5

Battery Data

Battery Specification	LiFePO4 6.4V
Battery Type	Lithium Iron
Nominal battery current	1.8Amp
Charge Current	250mA
Recharge Time	24hrs
Battery Total Weight(kg)	0.084

Thermals

Insulation Coverage	Do not cover with insulation
Operating Temperature Range °C	0 to +50

Construction

Primary Material	Polycarbonate
------------------	---------------

Packaging

Product carton overall dimensions(cm)	26.5(L)x12.5(W)x4.5(H)
Product Packaged Weight(kg)	0.56
Quantity Per Outer Carton	20
Outer carton(L)- cm	38
Outer carton(W)- cm	29
Outer carton(H)- cm	18

Outer carton Net weight- kg	11.2
Outer carton Gross weight- kg	11.7
Product Bar Code EAN-13 Number	5052544121852
Outer carton Bar Code ITF-14 Number	15052544121859

Standards & Approvals

Manufactured in accordance to

CE Marked

UKCA Marked

Date code/Purchase order No.

WEEE symbol

Certificate Of Conformity

Accredited Members

BS EN 60598:2015, 2-22

Yes

Yes

Yes

Yes

Available on request

LIA, ISO9001-2015, ISO14001-2015



