

JC100100

Skypack Pro

Skypack™ Pro 4ft Single 20W IP20 4000K WOP

Features & Benefits

- Intelligent press release buttons for simple installation
- Suspended LED tray for easy installation
- Press fit terminals loop in loop out with multiple position options
- Rear and end conduit entry points
- Plug and play Emergency and Microwave on/off modules
- Flexible cross mount fixing points
- Keyhole BESA mounting points
- Pre-moulded two way cable restraints
- Improved funnel clip in end caps for ease of installation





General Information

| Mounting | Surface/Suspended |
|------------------------------|--|
| Environment | Indoor |
| Color Finish | White |
| Product Shape | Rectangular |
| Product Range | Skypack™ Pro |
| Overall Dimensions | 1220 x 73.4 x 70 |
| Length (mm) | 1220 |
| Width (mm) | 73.4 |
| Height (mm) | 70 |
| Product Weight(kg) | 1.430 |
| Light Source | LED |
| Light Source Features | Neutral White |
| Luminaire Accessories | Suspension kit (JC100160) |
| Recommended product location | Domestic, Commercial and Industrial Applications |
| Method of fix | Surface or Suspended |
| Distance from lighted object | 0.3m |
| IP Rating | IP40 (Surface Mount) IP20 (Suspended) |
| Origin of manufacturer | Made in China |

| 5 Year Warranty (See Website for terms and conditions) |
|--|
| JCL |
| Runlite 2835 |
| 9405119090 |
| |

Electrical

| Voltage Rating | 220-240 |
|--------------------------------------|-------------------------------|
| Primary Running Current(Amp) | 0.12A |
| Inrush current(Amps) | <20A @240Vac |
| Operating Frequency Hz | 50/60Hz |
| Secondary running current(mA) | 350 |
| Constant Current or Constant Voltage | СС |
| Luminaire Circuit Wattage | 20 |
| Class | I |
| Output Voltage Max/Range (VDC) | 40-56 |
| Total Harmonic Distortion (THD)% | <20%@220-240Vac, 80-100% Load |
| EMC Compliant (EN55015) | Yes |
| Power Factor Correction | 0.9 |
| Input Electrical Connections | Live, Earth & Neutral |
| | |

Thermals

| Operating Temperature Range °C | -20°C~50°C |
|--------------------------------|------------|
|--------------------------------|------------|

Performance Data

| LED Life (Hours)* | 60000 |
|---|---|
| Energy Rating | This product contains a light source of energy efficiency |
| | class C |
| Actual Lumen Output | 2950 |
| Lumens Per Circuit Watt | 148 |
| Standard Deviation Colour Matching - SDCM | 1.6 |
| Color Rendering Index | 80-89 |
| CRI: Ra | 80 |
| Correlated Color Temperature | 4000K |
| Beam Angle ° | 120 |
| LOR (Light Output Ratio) % | 100 |
| Photometry Available | Yes: available on request. |
| | |

Construction

| Primary Material | Steel |
|------------------|---------------|
| Outer Diffuser | Polycarbonate |


Packaging

| Product carton overall dimensions(cm) | 125.5 x 8.5 x 8 |
|---------------------------------------|-----------------|
| Product Packaged Weight(kg) | 1.6600 |


| Quantity Per Outer Carton | 9 |
|-------------------------------------|----------------|
| Outer carton(L)- cm | 127.00 |
| Outer carton(W)- cm | 25.5 |
| Outer carton(H)- cm | 27.5 |
| Outer carton Net weight- kg | 14.94kg |
| Outer carton Gross weight- kg | 15.67kg |
| Product Bar Code EAN-13 Number | 5052544120879 |
| Outer carton Bar Code ITF-14 Number | 15052544120876 |
| | |

Standards & Approvals

| Manufactured in accordance to | BS EN 60598:2015, 2-1 |
|-------------------------------|----------------------------------|
| CE Marked | Yes |
| UKCA Marked | Yes |
| Date code/Purchase order No. | Yes |
| WEEE symbol | Yes |
| Certificate Of Conformity | Available on request |
| Accredited Members | LIA, ISO9001-2015, ISO14001-2015 |



















*Hours life stated is an indication of expected L70 chip and light output calculations when operating in optimum conditions. Product warranty period supports the full product during the term given. The L70 hours expectancy is not correlated with the full product warranty term, nor is it a representation of lumen depreciation during the warranty period.

**JCC Lighting Limited makes every effort to ensure that the Customs Tariff information in this document is timely and accurate. However, it's not possible for us to assure the absolute veracity and completeness of that information, as errors may occur. The placement of any inaccurate tariff information is completely unintentional. JCC Lighting Limited reserves the right, in its sole discretion, to correct any errors or omissions to the tariff code and to make any and all changes contained in this document at any time and without notice. It is the sole responsibility of the importer to ensure that the commodity code advised is correct for the products/goods being supplied by JCC Lighting Limited. JCC Lighting Limited does not assume any liabilities, losses, costs, and expenses arising out of or related to the importers use of this commodity code or the information related to the import of any JCC Lighting products.

JCC Lighting LTD, Lux Park, Chichester Business Park, City Fields Way, Tangmere, Chichester, West Sussex, PO20 2FT. Sales: 01243 838999 (8am to 5pm Monday to Friday) Fax: 01243 838998 | <u>sales@jcc.co.uk</u> | <u>www.jcc.co.uk</u> Company Registration Number: 03044848 | VAT Number: 918544112

This document is uncontrolled if printed, all information is subject to change

Version 123 [25/07/2024]